



5~15 W Switching Adapter (Wall Mount)

15 W  
**EDA-EA1015** series



**Features :**

- . CISPR 22'B', VccIB', Fcc'B' Compliance
- . EN60950 : UL,cUL, TUV, CE, CB
- . Over-voltage Protective installation
- . Short-circuit protective installation
- . Protection type : auto-recovery
- . 100% full load burn-in test

**1 year warranty**



Specifications	EA1015 A	EA1015 B	EA1015 C	EA1015 D
Input Voltage	90~264 VAC			
Input Frequency	47~63Hz			
Input Current	0.5A max.			
Inrush Current	60A max.			
Line Regulation	2% max.			
Output Voltage	3~6 VDC	6~9 VDC	9~15VDC	16~24VDC
Output Current	2A , 10W max.	1.5A, 15W max.	1.25A , 15W max.	1A , 15W max.
Load Regulation	±5%			
Ripple & Noise	1% Typical			
Efficiency	80% Typical			
Temperature Coefficient	0.05%/°C			
Over-Voltage Protection	Yes			
Operating Temperature	0~40°C			
Storage Temperature	-20~+85°C			

**Designation rule :**

**EDA-EA1015x-zY Series**



x : A~D, different output range from 3VDC to 24VDC

z : 1, Straight type  
2, Right angle type

Y : AC Plug type  
U, US type  
E, Europe type  
A, Australia type



**CASE : A U.S.A TYPE**

**CASE : A EUR. TYPE**



**CASE : B U.S.A TYPE**

**CASE : B EUR. TYPE**



Case Size A: 60x43.5x28  
Case Size B: 71x47.5x34.5