



Features :

- . Universal AC input range / full range
- . Short circuit, over-voltage protected (auto recovery)
- . Approvals : UL / cUL / TUV / CB / BSMI / CE
- . Built-in EMI filter, low ripple noise
- . Compact size
- . 100% full load burn-in test

1 year warranty



	EA10953(2)A			EA10953(2)	
DC output voltage range	+12~17V			+18~24V	
Output rated current	6.6A max			4.75A max	
Output rated power	80W max			90W max	
Input voltage	90~264VAC				
Input frequency	47~63Hz				
Input current	2A max.				
Inrush current	80A max.				
Line regulation	2% max.				
Load regulation	5%				
Ripple & Noise	1% typical				
Efficiency	83%			85%	
Temperature coefficient	0.05%				
Over-voltage protection	16~22V maxi			24~32V maxi	
AC inlet type	IEC320 C8 ( 2pins ) or IEC 320C6, C14 ( 3 pins )				
Input voltage range	90~264VAC	90~264VAC	90~264VAC	90~264VAC	90~264VAC
Working temp. & humidity	0°C~+40°C ( no derating by UL, cUL, TUV approved ), 20%~90% R.H.				
Storage temp. & humidity	-20°C~+85°C, 10%~95% R.H. ( non-condensing )				
Dimensions	133 x 59 x 33.5 mm ( Length x Width x Height )				
Weight	0.22 Kg				
Safety standards	UL, cUL, TUV, CB, PSE, LPS, EK, BSMI, 3C, CE approved				
EMC regulation	meets FCC Part 15 ClassB, CISPR22 ClassB, Vcci ClassB				